

JAC
MOTORS



JAC N55 EV TRUCK

SPECIFICATIONS

EASY242.COM

N55 EV

N55 EV TRUCK

N55 EV

DESCRIPTION		N55 EV RHD
Basic Information	Code	X5011
	Cab type	Single
	Product model	HFC1073EV1
	Left or Right driver	Left
	Applicable Temperature	'-5-40°C
	Target Market	
	Sold market	
Sold Remarks	In R&D	
Vehicle Parameters	Length/Width/Height (mm)	-
	Chassis Dimension (mm)	5995x2160x2323
	Wheelbase (mm)	3365
	Front-rear tread (mm)	1680/1705
	Front-rear suspension (mm)	1110/1520
	Approach angle	25
	Departure angle	16
	Min turning radius (m)	15
	Tire type	215/75 R17.5
	GVW (kg)	5500
	Front/Rear axle rated payload (kg)	3100/4500
	Rear axle ratio	5,571
	Leaf spring number	3/4+3
	Curb Weight (kg)	2950 (C/C)
Min ground clearance (mm)	228	
Vehicle Performance	Range under C-WTVC (km)	≥200 (C-WTVC)
	Range under constant speed @ 40/60 km/h (km)	/
	Max speed (km/h)	90
	Max gradability (%)	30%
	Acceleration performance from 0-50km/h (s)	<9 (s)
Powertrain System	Driving motor type	Permanent magnet synchronous motors
	Motor model	TZ368XSM726F
	Rated-peak power (kW)	65/130
	Rated-power rotational speed	1500/4500
	Rated-peak torque (N.m)	415/1200
	Cooling method	Liquid cooling
Electric Power System	Battery type	lithium iron phosphate battery
	Single cell type	/
	Rated voltage of the battery (V)	537.6
	Operating voltage range (V)	420 ~ 537.6 ~ 613.2
	Battery capacity (Ah)	180
	Total capacity (kW h)	96.77
	Weight of the battery (kg)	728
Combination method	6P6S	

DESCRIPTION		N55 EV RHD
Suspension	Front Suspension	Fewer springs of front cross-section + double acting shock absorber
	Rear Suspension	Rear leaf spring suspension (multi springs) + double acting shock absorber
Frame	Frame Cross Section Size	214*70*5
Brake	Type	Hydraulic
	Brake Type	Front drum, Rear drum
	SABS	-
	ABS	●
	HSA	-
Braking energy recovery	●	
Exterior	Manual headlamps with electrical control function	●
	Halogen headlamps	●
	Front/rear fog lamps	●
	Daytime running lights	●
	Power window	●
Interior	Roof storage (driver + co-driver)	●
	Storage	●
	Leather Seats	●
	Ash pan	●
	Driver sun visor	●
	Co-driver sun visor	●
	Sun visor with bill fold for driver & co-driver	●
	PVC carpet	●
	Cigarette lighter	●
Integralttype roof	●	
Safety	Driver's safety belt with adjustable height	●
	Three-point safety belt for co-driver	●
	Driver safety belt warning	●
	Airbag	●
	Auto unlock upon collision	●
	Reversing radar	●
	PVC carpet	●
	Cigarette lighter	●
	Integralttype roof	●
Comfort Configuration	AC	●
	Central locking	●
	Mechanical foldable remote control key	●
	Mp5	●
	USB interface	●
	AC charging	●
	Charging standard	CCS2
AC charging (slow charging) (h)	16	
DC charging (fast charging) (h)	●	
Charging standard	CCS2	
DC charging (fast charging) time (h)	2 hours, with charging ≥90kW	
	LJ1EKCBS	



Note: ● standard; ○ optional; - not available

BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

EASY CAR SALES